



## 2024 Class Rules

# Minimum Safety Requirements (All Classes)

**1 piece race suit** – 2-layer SFI / FIA rated race suits must be worn.

**Helmet** – Must be Snell / FIA rated and in good condition.

**Head and Neck restraint** – “Donut” Style is a bare minimum accepted, we will be looking to phase these out in the next year and enforce the use of HANS devices.

**Eye Protection** – Safety glasses if wearing open face / helmet visor acceptable.

**Harnesses** – minimum of a 4pt harness in good condition ie no frayed fibres, clean and mounted securely. We recommend the use of 5pt or 6pt harnesses.

**Window Nets** – must not be able to get any limbs out of the gap while harnessed into the seats.

**Fire Extinguishers** – minimum of 2kg per vehicle.

### First Aid Kit

**Roll cage** – minimum of 6-point roll cage, mounted safely, in good condition with good welding and design. Gussets where required.

**Seats** - must use a race seat from a reputable manufacturer and be mounted securely using metal components only. NO plastic components allowed, even if originally supplied by the manufacturer.

**Roof** – all vehicles must have a roof over the occupant's head. Minimum of 1mm steel or 3mm alloy.

**Fuel** – securely mounted fuel tank, leak free and in good condition. Alloy tanks to be phased out end of 2024. We strongly encourage the use of plastic fuel cells / safety fuel cells for petrol vehicles.

**Kill Switch** – all vehicles require a kill switch that turns off the engine when in the “off” position. This must be easily reached by driver and co-driver.

**Breakdown Safety device** – All vehicles must carry a reflective breakdown “triangle” or equivalent.



## 2024 Class Rules

# Unlimited Class / 4400

### ENGINE

- Any and all engines are permitted.

### TRANSFER-CASE

- Any and all transfer-cases are permitted.

### DRIVESHAFTS & AXLES

- Any and all driveshafts and axles are permitted.

### STEERING

- Any and all steering components and configurations are permitted. Rear steering is permitted.

### SUSPENSION

- Any and all suspension components and configurations are permitted.
- Shock absorbers of any make/model/type are permitted and may be installed in any location and orientation.
- Manual suspension controls (e.g., forced hydraulics) are permitted.

### TYRES

- Any and all tyres are permitted.

### SHARK FIN NUMBERS

- Shark Fin numbers must be 7" (175mm) tall with 1" (25mm) brush stroke in Arial Narrow font only. Front facing and rear facing numbers must be 6" (150mm) tall.
- 4400 Class: Black numbers with white background.